

# Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

<b>Manufacturer</b>	<b>Yesha Electricals Pvt Ltd</b>
<b>Address</b>	C-2/18 Industrial Estate Gorwa Road, Dist.Vadodara, 390016, India
<b>Type</b>	Cable Ties
<b>Description</b>	Roller Ball (SS) Coated/Uncoated Ladder (ST) Coated/Uncoated Releasable (RCT) Coated/Uncoated
<b>Trade Name</b>	Yesha Stainless Steel Cable Ties
<b>Application</b>	Intermediate clips for cable bundles for marine, offshore and industrial electrical installations.
<b>Specified Standard</b>	UL 62275.
<b>Ratings</b>	See Appendix.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

**Previous Version:** 00/00146(E3)

---

# Type Approval Certificate

The Design Appraisal Document LR21117954DA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

---

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



### **Appendix**

Type	Tie width / mm	Tie length / mm	Min. tensile strength – coated / N	Min. tensile strength – uncoated / N
Roller Ball (SS) Coated/Uncoated	4.6	100-1600	778	778
	7.9	100-1600	1112	1112
	12.0	100-1600	1335	1117
	16.0	100-1600	2002	4005
Ladder (ST) Coated/Uncoated	7.0	100-1600	529	529
	12.0	100-1600	778	778
Releasable (RCT) Coated/Uncoated	5.0	100-1600	1335	1779
	10.0	100-1600	1559	2002